

PRESSURE TREATED LUMBER

ACQ PRESERVED WOOD PRODUCTS



Product Information

NatureWood preserved wood is offered as an alternative to traditional CCA pressure treated wood. The NatureWood wood preservative is a waterborne, alkaline copper quaternary preservative system developed to provide long-term protection of wood exposed in exterior applications. The NatureWood system is based on the well-established effectiveness of copper combined with an organic quaternary compound and is applied to wood by pressure treatment. Copper and quaternary compounds provide protection from a broad spectrum of fungi and termites. The preservative technology in NatureWood products has been commercially used since 1991 in Europe, Asia, and the U.S.. For many backyard and commercial projects such as decks, fences and landscaping, NatureWood products are an ideal alternative to traditional pressure treated wood.



Sizes In Stock at Ring's End

Dried After Treatment	SIZES	8ft.	10ft.	12ft.	14ft.	16ft.
C & BETTER GRADE 5/4" DECKING	5/4" x 4"	-----	-----	8⁴⁰ _{ea.}	-----	12⁶⁴ _{ea.}
	5/4" x 6"	7⁸⁴ _{ea.}	10⁰⁰ _{ea.}	12³⁶ _{ea.}	12³² _{ea.}	16⁸⁰ _{ea.}

Dried After Treatment	SIZES	8ft.	10ft.	12ft.	14ft.	16ft.	18ft.	20ft.
#ONE PRIME GRADE SELECT WOOD	2" x 4"	5³⁶ _{ea.}	6⁰⁰ _{ea.}	7²⁰ _{ea.}	8²⁶ _{ea.}	10⁵⁶ _{ea.}	-----	-----
	2" x 6"	7⁶⁰ _{ea.}	9⁰⁰ _{ea.}	11⁰⁴ _{ea.}	13³⁰ _{ea.}	15²⁰ _{ea.}	-----	21⁶⁰ _{ea.}

No. 1 Grade	SIZES	8ft.	10ft.	12ft.	14ft.	16ft.	18ft.	20ft.
COMMONWEALTH #ONE LUMBER	2" x 8"	8⁶⁴ _{ea.}	10⁵⁰ _{ea.}	12⁶⁰ _{ea.}	14⁷⁰ _{ea.}	16⁸⁰ _{ea.}	-----	22⁰⁰ _{ea.}
	2" x 10"	10⁸⁰ _{ea.}	14⁵⁰ _{ea.}	17⁴⁰ _{ea.}	20³⁰ _{ea.}	21⁶⁰ _{ea.}	-----	28⁰⁰ _{ea.}
	2" x 12"	14⁰⁰ _{ea.}	-----	21⁰⁰ _{ea.}	-----	28⁰⁰ _{ea.}	-----	42⁰⁰ _{ea.}
	4" x 4"	10⁴⁰ _{ea.}	13⁵⁰ _{ea.}	15⁶⁰ _{ea.}	-----	22⁴⁰ _{ea.}	-----	-----
	4" x 6" <small>may contain #2 grade</small>	-----	-----	21⁶⁰ _{ea.}	-----	28⁸⁰ _{ea.}	-----	-----
	6" x 6" <small>may contain #2 grade</small>	21⁹⁹ _{ea.}	25⁵⁰ _{ea.}	33⁶⁰ _{ea.}	-----	45⁶⁰ _{ea.}	71¹⁰ _{ea.}	-----

- Excellent Dimensional Stability
- "Cleaner" than other No. 1 Grades



Use hot-dip galvanized, stainless steel, or other fasteners as recommended by the fastener manufacturer.

SQUARE BALUSTERS

2" x 2" x 3' **1⁵⁰**_{ea.} • 2" x 2" x 4' **2⁰⁰**_{ea.} • 2" x 2" x 8' **4⁰⁰**_{ea.}