



Safety Data Sheet according to 29 CFR 1910.1200(g)
KEIM Mineral Coatings of America, Inc
Revision date: 28.09.2020 Revision No: 1,0
KEIM EXTERIOR MINERAL BONDING PRIMER
0503-0144_US

1. Identification

Product identifier

KEIM EXTERIOR MINERAL BONDING PRIMER

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

Bonding Primer

Details of the supplier of the safety data sheet

Company name: KEIM Mineral Coatings of America, Inc
Address: 10615 Texland Boulevard, #600
USA Charlotte, NC 28273,
Telephone: 1 704-588-4811

Emergency phone number: in US and Canada:
1 800 535 5053 (INFOTRAC)

2. Hazard(s) identification

Classification of the chemical

29 CFR Part 1910.1200

This mixture is not classified as hazardous in accordance with Regulation 29 CFR 1910.1200(d).

Label elements

Additional advice on labelling

The product does not require a hazard warning label.

Hazards not otherwise classified

Handle in accordance with good industrial hygiene and safety practice.

3. Composition/information on ingredients

Mixtures

Chemical characterization

Sol-Silicate-based paint for outdoor use, with light resistant, inorganic pigments and mineral fillers.

4. First-aid measures

Description of first aid measures

General information

No special measure necessary.
Show this safety data sheet to the doctor in attendance.

After inhalation

Take affected person into fresh air.
In the event of symptoms refer for medical treatment.

After contact with skin

Wash off with soap and plenty of water.
Consult a doctor if skin irritation persists.
Do not use solvents or thinners.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Rinse out mouth and give plenty of water to drink.





Safety Data Sheet according to 29 CFR 1910.1200(g)
KEIM Mineral Coatings of America, Inc
Revision date: 28.09.2020 Revision No: 1,0
KEIM EXTERIOR MINERAL BONDING PRIMER
0503-0144_US

Do not induce vomiting.
Call a physician immediately.

Most important symptoms and effects, both acute and delayed

OSHA Hazard Communication: This material is not considered hazardous by the OSHA Hazard Communication Standard 29CFR 1910.1200.

No data available.

Indication of any immediate medical attention and special treatment needed

Treat symptoms.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Product itself does not burn. Fire-extinguishing activities according to surrounding building materials.

Specific hazards arising from the chemical

In case of fire and/or explosion do not breathe fumes.

Special protective equipment and precautions for fire-fighters

Use breathing apparatus with independent air supply.

Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing.
Ensure adequate ventilation. Keep away noninvolved persons.
High risk of slipping due to leakage/spillage of product.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal.

Clean contaminated surface thoroughly.

Reference to other sections

Information for disposal look up chapter 13.

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Avoid contact with skin, eyes and clothing.
Keep container tightly closed.
Avoid formation of aerosolized spray mist.
Keep a good ventilation and air-exhaust at the place of work.

Advice on protection against fire and explosion

No special measure necessary.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in unopened original container. Keep in a dry, cool and well-ventilated place.

Hints on joint storage

Do not store with acids.





Safety Data Sheet according to 29 CFR 1910.1200(g)
KEIM Mineral Coatings of America, Inc
Revision date: 28.09.2020 Revision No: 1,0
KEIM EXTERIOR MINERAL BONDING PRIMER
0503-0144_US

Further information on storage conditions

To be kept tightly closed, in a cool and dry place.
Keep from freezing.
Protect from heat and direct solar radiation.

8. Exposure controls/personal protection

Control parameters

Exposure limits

CAS No.	Substance	ppm	mg/m ³	f/cc	Category	Origin
7727-43-7	Barium sulfate (resp)	-	5		TWA (8 h)	REL
7727-43-7	Barium sulfate (inhalable fraction)		5		TWA (8 h)	ACGIH-2020
7727-43-7	Barium sulfate Respirable fraction	-	5		TWA (8 h)	PEL
7631-86-9	Silica, amorphous	-	6		TWA (8 h)	REL
14808-60-7	Silica, crystalline (as respirable dust)	-	0.05		TWA (8 h)	REL
14808-60-7	Silica, crystalline - alpha-quartz (respirable fraction)		0.025		TWA (8 h)	ACGIH-2020
14808-60-7	Silica, crystalline quartz, total dust	-	(Z-3)		TWA (8 h)	PEL

Exposure controls

Protective and hygiene measures

Do not inhale aerosolized spray mist.
Take off immediately all contaminated clothing.
Avoid contact with skin, eyes and clothing.
Wash hands before breaks and at the end of workday.

Eye/face protection

Eye wash bottle with pure water.
Tightly fitting goggles.

Hand protection

Chemical-resistant gloves (EN 374) / NIOSH/MSHA approved
Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes. Select the appropriate glove material adhering to the breakthrough time, permeation rate and the degradation.

Skin protection

Long sleeved clothing.

Respiratory protection

Not required; except in case of aerosolized spray mist.
Mask with filter Type P (EN 141), NIOSH/MSHA approved

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Pasty
Color: White
Odor: Odorless
pH-Value (at 20 °C): ~11

Changes in the physical state

Flash point: None





Safety Data Sheet according to 29 CFR 1910.1200(g)
KEIM Mineral Coatings of America, Inc
Revision date: 28.09.2020 Revision No: 1,0
KEIM EXTERIOR MINERAL BONDING PRIMER
0503-0144_US

Based on available data, the classification criteria are not met.

Carcinogenicity (NTP): Not listed
Carcinogenicity (IARC): Not listed
Carcinogenicity (OSHA): Not listed

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

Health injuries are not known or expected under normal use.

12. Ecological information

Ecotoxicity

No toxicological data available.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Slightly water hazardous.

Further information

Do not flush into surface water or sanitary sewer system. A pH-change becomes possible in water.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Disposal in accordance with local regulations.

Contaminated packaging

Disposal in accordance with local regulations.

Cleaning agent: Water

14. Transport information

US DOT 49 CFR 172.101

Proper shipping name: Not regulated.

Marine transport (IMDG)

Marine pollutant: no

Other applicable information (marine transport)

Non hazardous material as defined by the transport regulations.

Air transport (ICAO-TI/IATA-DGR)

Other applicable information (air transport)

Non hazardous material as defined by the transport regulations.

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.





Safety Data Sheet according to 29 CFR 1910.1200(g)
KEIM Mineral Coatings of America, Inc
Revision date: 28.09.2020 Revision No: 1,0
KEIM EXTERIOR MINERAL BONDING PRIMER
0503-0144_US

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

The transport takes place only in approved and appropriate packaging.

15. Regulatory information

U.S. Regulations

National Inventory TSCA

All of the components are listed on the TSCA inventory.

State Regulations

Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

16. Other information

Hazardous Materials Information Label (HMIS)

Health: 1
Flammability: 0
Physical Hazard: 0

NFPA Hazard Ratings

Health: 1
Flammability: 0
Reactivity: 0
Unique Hazard:



Changes

Revision date: 28.09.2020
Revision No: 1,0
Changes in section: 1

Abbreviations and acronyms

IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
DOT = Department of Transportation
TDG = Transport of Dangerous Goods

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
CAS = Chemical Abstract Service
ISO = International Organization for Standardization
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Other data

The information in this document is based on the present state of knowledge and is applicable to the product with regard to appropriate safety precautions.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)





Safety Data Sheet according to 29 CFR 1910.1200(g)
KEIM Mineral Coatings of America, Inc
Revision date: 28.09.2020 Revision No: 1,0
KEIM EXTERIOR MINERAL BONDING PRIMER
0503-0144_US

