

Printing Date 06/10/2015 Revision Number 1 Revision Date 06/10/2015

## 1 Identification

- · Product identifier
- · Trade name: Kleer Cellular PVC Laminating Adhesive, Part B
- · Relevant identified uses of the substance or mixture. Activator
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Extreme Adhesives, LLC

A Division of Royal Adhesives & Sealants, LLC

63 Epping Road

Raymond, NH 03077

800-888-4583

- · Information department: Environment protection department.
- · Emergency telephone number:

ChemTrec: Day or Night within USA and Canada: 1-800-424-9300. Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

H402 Harmful to aquatic life.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

Highly flammable liquid and vapor.

Harmful to aquatic life.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

 $Use\ explosion-proof\ electrical/ventilating/lighting/equipment.$ 

 $We ar \ protective \ gloves \ / \ eye \ protection \ / \ face \ protection.$ 

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

(Contd. on page 2)

Printing Date 06/10/2015 Revision Number 1 Revision Date 06/10/2015

### Trade name: Kleer Cellular PVC Laminating Adhesive, Part B

(Contd. of page 1)

Avoid release to the environment.

Take precautionary measures against static discharge.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 2

· HMIS-ratings (scale 0 - 4)



 $\frac{2}{1}$  Health = 2

Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture

· Hazardous co	mponents:
----------------	-----------

	F	
80-62-6	methyl methacrylate	25-50%
13463-67-7	titanium dioxide	2.5-10%

## 4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.

· After swallowing:

Rinse out mouth with water. Drink 1 - 2 glasses of water but DO NOT induce vomiting. Do not give liquids to a drowsy, convulsing or unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Seek medical treatment.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Printing Date 06/10/2015 Revision Number 1 Revision Date 06/10/2015

Trade name: Kleer Cellular PVC Laminating Adhesive, Part B

(Contd. of page 2)

\*

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Foam

CO2, sand, extinguishing powder. Do not use water.

- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Protective clothing and respiratory protective device.

\*

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste in accordance with federal state and local regulations.

 $Ensure\ a dequate\ ventilation.$ 

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

\*

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Avoid prolonged or repeated contact with skin.

Avoid contact with eyes.

Wash thoroughly after handling.

Handle/process in well ventilated areas.

Open containers in a well ventilated area and avoid breathing headspace vapors.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep container closed when not in use.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store at temperatures not exceeding 37.7C

Store in a cool location away from direct heat.

- Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions:

Protect from contamination.

Store in dry conditions.

Keep receptacle tightly sealed.

(Contd. on page 4)

Printing Date 06/10/2015 Revision Number 1 Revision Date 06/10/2015

Trade name: Kleer Cellular PVC Laminating Adhesive, Part B

(Contd. of page 3)

 $\cdot$  Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

### · Components with limit values that require monitoring at the workplace:

### 80-62-6 methyl methacrylate

PEL Long-term value: 410 mg/m³, 100 ppm REL Long-term value: 410 mg/m³, 100 ppm TLV Short-term value: 410 mg/m³, 100 ppm Long-term value: 205 mg/m³, 50 ppm

(SEN) NIC-DSEN

#### 13463-67-7 titanium dioxide

PEL Long-term value: 15\* mg/m<sup>3</sup>

\*total dust

REL See Pocket Guide App. A

TLV Long-term value: 10 mg/m³ withdrawn from NIC

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

### · Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing Date 06/10/2015 Revision Number 1 Revision Date 06/10/2015

Trade name: Kleer Cellular PVC Laminating Adhesive, Part B

(Contd. of page 4)

• Eye protection: Safety glasses with side shields.



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and c	hemical properties
General Information	
Appearance:	
Form:	Paste
Color:	white - Yellow-brown
Odor:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point:	Undetermined.
Boiling point:	101 °C (214 °F)
Flash point:	10 °C (50 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	430 °C (806 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Flammable limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
Vapor pressure at 20 °C (68 °F):	47 hPa (35 mm Hg)
Specific gravity at 20 °C (68 °F):	0.97 g/cm³ (8.095 lbs/gal)
Relative density	Not determined.
Vapour density	>1 at 20C
Evaporation rate	3
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	0.0 %

Printing Date 06/10/2015 Revision Number 1 Revision Date 06/10/2015

Trade name: Kleer Cellular PVC Laminating Adhesive, Part B

(Contd. of page 5)

· Other information

Mixed product VOC content: <50 g/l

## 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Heat, flames, sparks, hot surfaces, ignition sources.

Direct sunlight

· Incompatible materials:

Strong oxidizers, acids, and bases.

Reacts with amines.

Reacts with moisture

reducing agents.

Reacts with ultraviolet radiation

· Hazardous decomposition products:

Nitrogen oxides

Carbon monoxide and carbon dioxide

Hydrogen cyanide (prussic acid)

Isocyanate

Hydrocarbons

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: May irritate the skin.
- · on the eve: May irritate the eye.
- · Sensitization: No sensitizing effects known.
- $\cdot \textit{Additional toxicological information:}$

The product is not subject to classification according to internally approved calculation methods for preparations:

· Carcinogenic categories

· IARC (Inter	national Agency for Research on Cancer)	
80-62-6	methyl methacrylate	3
13463-67-7	titanium dioxide	2B
· NTP (Nation	nal Toxicology Program)	
None of the	ingredients is listed.	
· OSHA-Ca (C	Occupational Safety & Health Administration)	
None of the	ingredients is listed.	

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.

(Contd. on page 7)

Printing Date 06/10/2015 Revision Number 1 Revision Date 06/10/2015

Trade name: Kleer Cellular PVC Laminating Adhesive, Part B

(Contd. of page 6)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

At present there are no ecotoxicological assessments.

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must be specially treated adhering to official regulations.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

	4 6				C	
_ / / /		MING	nort		OFW	atton
			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			ation
			7	~~,	~	

	IIN_	M	nher
•	( / / V =	IVILI	mner

· DOT, ADR, IMDG, IATA

UN1133

· UN proper shipping name

 $\cdot DOT$ 

Adhesives

· ADR · IMDG, IATA 1133 Adhesives mixture ADHESIVES mixture

- · Transport hazard class(es)
- $\cdot DOT$



· Class 3 Flammable liquids

· Label

· ADR, IMDG, IATA



· Class 3 Flammable liquids

· Label

· Packing group

· DOT, ADR, IMDG, IATA

(Contd. on page 8)

Printing Date 06/10/2015 Revision Number 1 Revision Date 06/10/2015

Trade name: Kleer Cellular PVC Laminating Adhesive, Part B

		(Contd. of page 7)
· Environmental hazards:	Not applicable.	
· Special precautions for user	Warning: Flammable liquids	
· Danger code (Kemler):	339	
· EMS Number:	F- $E$ , $S$ - $D$	
· Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	
· UN ''Model Regulation'':	UN1133, Adhesives mixture, 3, II	

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 methyl methacrylate

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

- · Proposition 65
- · Chemicals known to cause cancer:

13463-67-7 titanium dioxide

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

· (DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· Cancerogenity categories

EDA (Euring and all Durkaski and Against)	
· EPA (Environmental Protection Agency)	
80-62-6 methyl methacrylate	E, NL
· TLV (Threshold Limit Value established by ACGIH)	
80-62-6 methyl methacrylate	A4
13463-67-7 titanium dioxide	A4
· MAK (German Maximum Workplace Concentration)	
13463-67-7 titanium dioxide	3A
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
13463-67-7 titanium dioxide	

- · National regulations:
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the

Printing Date 06/10/2015 Revision Number 1 Revision Date 06/10/2015

Trade name: Kleer Cellular PVC Laminating Adhesive, Part B

(Contd. of page 8)

completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- · Department issuing SDS: Environment protection department.
- · Creation Date: 06/10/2015
- · Date of preparation / last revision 06/10/2015 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) Flam. Liq. 2: Flammable liquids, Hazard Category 2

: Hazardous to the aquatic environment - AcuteHazard, Category 3

USA