DRYLOK® EXTREME **CONCRETE & MASONRY** WATERPROOFER





Unlike ordinary paint that simply adheres to a surface and can be forced off by incoming water pressure, DRYLOK® Extreme Concrete & Masonry Waterproofer actually penetrates the pores in that surface, bonding to the masonry and creating an impenetrable barrier.

This product is an essential part of the waterproofing process. • Prepare • Patch • Waterproof

FEATURES:

Formula: latex base

Finish: bright white flat, smooth

Application tools: brush, roller or sprayer

(For spray specifications visit www.DRYLOK.com)

Location: interior, exterior, below, above grade

Where to use: basements, retaining walls, cement stucco, foundations,

fountains, bare concrete, swimming pools, and more

Optional: if top-coating wait 24 hours

conforms to ASTM D-7088 Resistance to Hydrostatic **Specifications:**

Pressure and ASTM D-6904 Resistance to Wind Driven Rain

07 14 16 COLD FLUID-APPLIED WATERPROOFING CSI Masterformat®:

> **07 19 00 WATER REPELLENTS 09 91 13 EXTERIOR PAINTING 09 91 23 INTERIOR PAINTING**



Minimum of 2 Coats



Soap and Water Clean up



75-100 Sq Ft Coverage per Gal



Bright White Tintable to a Maximum of 2 oz. of Colorant per Gal

BENEFITS

- GUARANTEED to withstand category 4 (140+ MPH) hurricane force winddriven rain – and 15 pounds of hydrostatic pressure (PSI).
- Fully transferable 15 Year Warranty
- Green Wise Certified
- Resists mildew on the dry paint film
- Helps protect against radon gas penetration by reducing vapor transfer
- Semi-Impermeable coating keeps water and vapor out (<1 perm rating) will not trap moisture in the masonry
- Listed in Masterspec® and BSD SpecLink®



45 Minutes To Touch, 2-3 Hr Dry Time, **2 Hr** Recoat Time



100 g/L VOC











Bright White/ Tint Base

1 QT. 4/Case......28612 1 GAL. 2/Case.......28613 5 GAL. 1/Unit 28615

NOTE: COLOR SWATCHES ARE REPRESENTATIONAL ONLY.

WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov





Gray

21913

n/a

n/a

