## DRYLOK® ORIGINAL **CONCRETE & MASONRY** WATERPROOFER





Unlike ordinary paint that adheres to a surface and can be forced off by incoming water pressure, DRYLOK® Original Concrete & Masonry Waterproofer penetrates the pores in that surface, bonding to the masonry and creating an impenetrable barrier.

This product is an essential part of the waterproofing process. • Prepare • Patch • Waterproof

## **FEATURES:**

Formula: latex base

flat white, sandy texture Finish:

**Application tools:** brush or roller

Location: interior, exterior, below, above grade

Where to use: basements, fish ponds, retaining walls, bird baths,

foundations, fountains, and more

**Optional:** if top-coating wait 24 hours

**Specifications:** conforms to ASTM D-7088 Resistance to Hydrostatic

Pressure and ASTM D-6904 Resistance to Wind Driven Rain

CSI Masterformat®: 07 14 16 COLD FLUID-APPLIED WATERPROOFING

**07 19 00 WATER REPELLENTS 09 91 13 EXTERIOR PAINTING** 

09 91 23 INTERIOR PAINTING



75-100 Sq Ft Coverage per Gal



Tintable to a Maximum of 2 oz. of Colorant per Gal

## **BENEFITS:**

- **GUARANTEED** to stop water withstands 10 pounds of hydrostatic pressure (PSI), equivalent to a wall of water 22 feet high
- Fully transferable 10 Year Warranty
- Helps protect against radon gas penetration
- Low-odor, water clean up, formula complies with all VOC requirements
- Semi-Impermeable coating keeps water and vapor out. (<1 perm rating) will not trap moisture in the masonry
- Listed in Masterspec® and BSD SpecLink®



1.5 Hrs To Touch, 2-3 Hr Dry Time, 2-3 Hr Recoat Time



100 g/L VOC





Minimum of 2

Soap and Water

Coats









1 QT. 4/Case.....27512 1 GAL. 2/Case......27513 2 GAL. 1/Unit . . . . . . . . . 27514 5 GAL. 1/Unit . . . . . . . . . 27515

NOTE: COLOR SWATCHES ARE REPRESENTATIONAL ONLY. **MARNING:** Cancer and Reproductive Harm – www.P65Warnings.ca.gov







